

**IN THE CLAIMS:**

Please amend claim 16, as set forth below.

1 1. (Original) An apparatus comprising:  
2 a housing having an access door, the access door movable between a closed position and  
3 an open position;  
4 a slot extending through the housing, the slot sized and located to receive a lock head of a  
5 locking device when the lock head exhibits a first orientation and to retain the  
6 lock head when the lock head exhibits a second orientation; and  
7 a latch assembly disposed in the housing to maintain the access door in the closed  
8 position when the lock head exhibits the second orientation.

1 2. (Original) The apparatus of claim 1, further comprising a removable  
2 component disposed in the housing adjacent the access door and accessible when the  
3 access door is in the open position.

1 3. (Original) The apparatus of claim 2, the removable component  
2 comprising a lamp assembly.

B3 C 4. (Original) An apparatus comprising:

2 a housing including an access door, the access door movable between a closed position  
3 and an open position;  
4 a slot extending through the housing, the slot sized and located to receive a lock head of a  
5 locking device when the lock head exhibits a first orientation and to retain the  
6 lock head when the lock head exhibits a second orientation;  
7 a latch to engage the access door and maintain the access door in the closed position  
8 when the latch is at a first position, the latch movable to a second position  
9 wherein the latch disengages the access door to enable the access door to move  
10 toward the open position; and  
11 a stop element disposed on the latch, the stop element to engage the lock head and to  
12 maintain the latch in the first position when the lock head exhibits the second  
13 orientation.

1 5. (Original) The apparatus of claim 4, the latch and stop element  
2 comprising an integrated part.

1 6. (Original) The apparatus of claim 4, further comprising a removable  
2 component disposed in the housing adjacent the access door and accessible when the  
3 access door is in the open position.

**B3** 1 7. (Original) The apparatus of claim 4, further comprising a biasing element  
2 to bias the latch toward the first position.

1 8. (Original) The apparatus of claim 4, further comprising at least one guide  
2 element disposed on the housing to restrict movement of the latch.

1 9. (Original) The apparatus of claim 4, further comprising a handle disposed  
2 on the latch and extending through an aperture in the housing.

1 10. (Original) The apparatus of claim 4, further comprising:  
2 a retaining element disposed on the latch; and  
3 a receptacle disposed on the access door, the receptacle sized and oriented to receive an  
4 end of the retaining element.

83 1 C 11. (Original) A projector comprising:  
2 a housing including an access door, the access door movable between a closed position  
3 and an open position;  
4 a lamp assembly disposed within the housing adjacent the access door;  
5 a slot extending through the housing, the slot sized and located to receive a lock head of a  
6 locking device when the lock head exhibits a first orientation and to retain the  
7 lock head when the lock head exhibits a second orientation;  
8 a latch to engage the access door and maintain the access door in the closed position  
9 when the latch is at a first position, the latch movable to a second position  
10 wherein the latch disengages the access door to enable the access door to move  
11 toward the open position; and  
12 a stop element disposed on the latch, the stop element to engage the lock head and to  
13 maintain the latch in the first position when the lock head exhibits the second  
14 orientation.

1 12 (Original) The projector of claim 11, the latch and stop element  
2 comprising an integrated part.

1 13. (Original) The projector of claim 11, further comprising a biasing element  
2 to bias the latch toward the first position.

14. (Original) The projector of claim 11, further comprising at least one guide  
element disposed on the housing to restrict movement of the latch.

15. (Original) The projector of claim 11, further comprising a handle  
disposed on the latch and extending through an aperture in the housing.

16. (Currently Amended) The ~~apparatus~~ projector of ~~claim 4~~ claim 11, further  
comprising:  
a retaining element disposed on the latch; and  
a receptacle disposed on the access door, the receptacle sized and oriented to receive an  
end of the retaining element.